# SUBMITTAL — AB&I Foundry Submittal Data

Date:	Job Name:	Location:	
Engineer:		Contractor:	



# No Hub Pipe and Fittings

1½" to 15" diameter. Soil waste, vent lines, rain water conductors and storm drainage lines shall be NSF Certified compliant and bear the registered trademark of Cast Iron Soil Pipe Institute indicating that these items are manufactured to CISPI Standard 301 and ASTM 888.

IAPMO File No. 3270



## **SV Hub & Spigot Pipe and Fittings**

Sizes 2" to 15". Soil waste, vent lines, rain water conductors and storm drainage lines shall be NSF Certified compliant and bear the registered trademark of the Cast Iron Soil Pipe Institute indicating that these items comply with ASTM A 74 and HS 74.



# **SV Hub & Spigot Pipe and Fittings**

Sizes 2" to 15". Soil waste, vent lines, rain water conductors and storm drainage lines shall be NSF Certified compliant and bear the registered trademark of the Cast Iron Soil Pipe Institute indicating that these items comply with ASTM A 74 and HS 74.



## TY-SEAL and EZ-TITE Gaskets

Sizes from 2" and 15" (TY-SEAL) and 2" to 6" (EZ-TITE) shall comply with all requirements of ASTM C 564.

IAPMO File No. 0391

#### SAMPLE SPECS

AB&I is pleased to provide suggested wording for specifications to ensure that the DWV material specified truly meets the requirements of the various standards for cast iron pipe and fittings.

For details, go to ABIFoundry.com







